



ENCORE | ARROW

- Hydro-Gear transmissions
- R.O.P.S. standard
- Triple layer spindle support
- Discharge, mulch, or collect





ENCORE | ARROW

STANDARD

Construction: #8 ga. fabricated steel

Cutting Heights: 1.5"-4.5"
in .5" increments

Travel Speed: 0-7 MPH forward
0-3.4 MPH reverse

PTO: Electric clutch

Final Drive: Integrated

Fuel Capacity: 4 gallons

MODEL EA46XS22KW

Deck: 46"

Engine: 21.5 HP*
Kawasaki FR651V

Transmission: Hydro-Gear EZT

Blades: 3-16" high lift

Blade Speed: 17,500 ft./min.

Front Wheels: 11-4.00 x 5 smooth

Drive Wheels: 18-9.50 x 8 turf

Width: 47.5"
59.9" w/deflect

Length: 71.7"

Weight: 544 lbs

MODEL EA50XL24KW

Deck: 50"

Engine: 23 HP*
Kawasaki FR691V

Transmission: Hydro-Gear ZT-2800

Blades: 3-17.3" high lift

Blade Speed: 17,600 ft./min.

Front Wheels: 13-5.00 x 6 smooth

Drive Wheels: 20-10.00 x 10 turf

Width: 51"
59" w/deflector

Length: 72"

Weight: 590 lbs

MODEL EA46XS22KW

Deck: 60"

Engine: 23 HP*
Kawasaki FR691V

Transmission: Hydro-Gear ZT-2800

Blades: 3-20.5" high lift

Blade Speed: 18,300 ft./min.

Front Wheels: 13-5.00 x 6 smooth

Drive Wheels: 20-10.00 x 10 turf

Width: 61"
68.5" w/deflector

Length: 72"

Weight: 637 lbs